

PLASTIC PIPES FOR PUBLIC GRAVITY FOUL SEWERS (ADOPTABLE) 100MM TO 300MM

KEY GUIDANCE DOCUMENTS

- Design and Construction Guidance - England
- Sewers for Scotland
- Sewers for Adoption 7 - Wales
- Sewers for Adoption (NI) – Northern Ireland



ACCESS POINTS

- Plastic chambers up to 3m depth to BS EN 13598-2
- Plastic manholes 3m to 6m depth to BS EN 13598-2

PIPES

You can use

- **Structured wall pipes (smooth outside)** stiffness SN8 to BS EN 13476-1 and BS EN 13476-2 and (for pipes ≥ 150 mm) to WIS 4-35-01
- **Structured wall pipes (profiled outside)** stiffness SN8 to BS EN 13476-1 and BS EN 13476-3 and (for pipes ≥ 150 mm) to WIS 4-35-01
- **Solid wall pipes** stiffness SN4 or SN8 to BS EN 1401-1 (PVC-U), BS EN 1852-1 (PP) or BS EN 12666-1 (PE)

INSTALLATION

Install pipes, chambers and ancillaries to BS EN 1610

Choose assured products with 3rd party certification to these standards supplied by BPF Pipes Group members

For further technical support please visit our website | bpfpipesgroup.com